

# iCLASS<sup>®</sup> OEM50 Module

Contactless Smart Card Module • Read/Write • Wiegand/TTL Interface • 3131



## ACCESS flexibility.

### Not Recommended for New Development

Designed for embedding into OEM equipment as a component in upper level assemblies, the iCLASS<sup>®</sup> OEM50 Module is a 13.56 MHz contactless smart card reader/writer in an extremely compact printed circuit board form factor.

The OEM50 enables iCLASS technology to be used for multiple applications including cashless vending, biometrics, time and attendance, alarm system control, HVAC control, process control, and point-of-sale terminals.

With only a two-wire serial interface and a regulated power supply, an OEM has the power of iCLASS at their fingertips.

The OEM50 is designed to operate with a wide variety of antenna configurations. HID offers optional antenna PCBs in 3.15" x 3.15" (80 mm x 80 mm) and 1.34" x 1.89" (34 mm x 48 mm) sizes, and also provides a comprehensive antenna design guide for OEMs. Separating the antenna from the module allows the OEM to make the most efficient use of available space, and allows the module to be installed in a metal enclosure while the antenna is remotely located behind a non-conductive bezel.

Inputs and outputs are all TTL level logic. Transient suppression, voltage regulation, and output drivers will be provided by the Host device. A user guide (Part Number 3131-901) provides complete interface specifications.

When used with iCLASS cards, the OEM50 offers security features such as RF data encryption and mutual authentication using 64-bit keys for each application area and optional DES or Triple DES data encryption for the HID application area. HID provides key management for access control and other data stored in the HID application area.

For access control applications, the OEM50 can read either iCLASS credentials (transmitting the Wiegand formatted data as encoded), MIFARE<sup>®</sup> Standard, Ultralight, or DESFire<sup>®</sup> credentials (transmitting Wiegand data based on the card serial number in 26-, 32-, 34-, 40-, or 56-bit formats). For non-access control applications, the OEM50 module can read or write to any application area on the iCLASS credential, with all reader functions controlled by an external Host processor via the TTL port using the iCLASS Serial Protocol.

The OEM50 has a logic level control output which can be operated by serial commands via the TTL port. This can be used to control external devices or audiovisual indicators with the appropriate driver circuitry.

When the configurable Hold Control Line is asserted, either all card reading is disabled or the module will buffer one card read and ignore subsequent reads until the line is released.

**Card Compatibility**

The iCLASS® OEM50 Module is compatible with all iCLASS credentials. The module's versatility allows it to read credentials meeting several ISO standards:

- 15693 – read/write (2k bit and 16k bit iCLASS credentials)
- 14443A - read only (MIFARE® card serial number)
- 14443B - read/write (16k bit iCLASS credential)

**Application Support**

HID offers Certification Training, as well as a Software Developer's Kit (available separately; consult factory for details). See HID Application Note 28 for details.

**Mounting**

The module can be mounted on standoffs, using the four slots located at each corner of the PCB, sized for a #2-56 screw (maximum screw head or standoff diameter is 0.20" or 5.0 mm). The module can also be mounted by installing PCB mount pin headers and installing compatible sockets on the host device.

Metal components located near the antenna may reduce the card reading distance of the module. The antenna will NOT read cards or tags if completely enclosed in a metal enclosure. (If a metal enclosure is required, the antenna can be remotely located behind a non-metallic bezel.)

**Environmental**

If used in outdoor environments, the module must be epoxy potted or installed in a watertight enclosure.

**Part Numbers**

Base Part Number: 3131  
Antennae: Consult Factory

**Options:**

Key Management - Standard or Custom  
Selectable Output Type (for MIFARE Cards)  
Standard Termination: none; solder pads and vias provided  
Programmable Control Output Operation (logic level)

**Typical Maximum Read Range**

Dependent upon antenna design, enclosure design, exciter voltage, materials used, and proximity of metal components.

**Dimensions**

PCB: 1.10" x 1.20" (27.94 mm x 30.48 mm)  
Large Antenna: 3.15" x 3.15" (80 mm x 80 mm)  
Small Antenna: 1.35" x 1.90" (34 mm x 48 mm)

**Component Height**

Top: 0.10" (2.5 mm) max  
Bottom: 0.10" (2.5 mm) max

**Material**

FR-4 Fiberglass laminate

**Power Requirements**

Nominal input: 5 VDC +/- 15%  
Regulated DC power required

**Input Voltage Range**

Processor: 5 VDC +/- 0.250 V  
Exciter: 4.75 - 8.0 VDC

**Current Requirements**

Peak current (based on exciter input)  
93 mAmp at 5 VDC; 121 mAmps at 8 VDC  
Average current: Consult Factory

**Operating Temperature**

-35° to 65° C (-31° to 150° F)

**Operating Humidity**

5% to 95% relative humidity non-condensing

**Weight**

Consult Factory

**Transmit Frequency**

13.56 MHz

**Pending Certifications**

cURus - UL Recognized for electrical safety  
(US and Canada) OEM or integrator must secure regulatory approvals for the entire integrated device, consisting of the module and OEM components.  
IP55

**Cable Distance**

I/O and power connections – 1' (30 cm)  
Wiegand/Serial TTL Interface – 1' (30 cm)  
Antenna Cable  
50-Ohm MCX Coax – Consult Factory  
24 AWG twisted pair – up to 3.0" (76 mm)

© 2009 HID Global. All rights reserved. HID, the HID logo, and iCLASS are trademarks or registered trademarks of HID Global in the U.S. and/or other countries. All other trademarks, service marks, and product or service names are trademarks or registered trademarks of their respective owners. Rev. 06/2009

MKT-OEM50\_DS\_EN



**ACCESS** experience.

[hidglobal.com](http://hidglobal.com)

**Corporate**  
**North America**  
15370 Barranca Pkwy  
Irvine, CA 92618  
U.S.A.  
Tel: 1 800 237 7769  
Tel: +1 949 732 2000  
Fax: +1 949 732 2360

**Asia Pacific**  
19/F 625 King's Road  
North Point  
Island East  
Hong Kong  
Phone: +852 3160-9800  
Fax: +852 3160-4809

**Latin America**  
Circunvalacion Ote. #201 B  
Despacho 2  
Col. Jardines del Moral  
Leon 37160, Gto.  
Mexico  
Phone: +52 477 779 1492  
Fax: +52 477 779 1493

**Europe, Middle East & Africa**  
Haverhill Business Park  
Phoenix Road  
Haverhill, Suffolk  
CB9 7AE  
England  
Tel: +44 (0) 1440 714 850  
Fax: +44 (0) 1440 714 840